

# PREMIUM PAR30 Pro

- 20W

- 32W

Non-dimmable



Website



Intelligent Driver

RA90 LM80



Article Code	TPAR30PRO-20W-XN	TPAR30PRO-32W-XN
Lamp Description	PREMIUM PAR30 20W NON-DIM	PREMIUM PAR30 32W NON-DIM
<b>GENERAL CHARACTERISTICS</b>		
Shape	PAR30	PAR30
Cap - Base	E27	E27
Rated Wattage	20 W	32 W
Input Voltage	220-240 Vac	220-240 Vac
Operating Frequency	50/60Hz	50/60Hz
Luminous Flux	2000 lm	3200 lm
Lifetime (hours)	25,000 hrs	25,000 hrs
Switching Cycles	50,000	50,000
Start Time from 0% to 100%	< 0.5 s	< 0.5 s
Power Factor	0.9	0.9
Working Temperature	-20°C ~ 35°C	-20°C ~ 35°C
Guarantee	3 years	3 years
Dimension	W:95mm x H:125mm	W:95mm x H:125mm
<b>LIGHT CHARACTERISTICS</b>		
Color	Warm White / Neutral White	Warm White / Neutral White
Color Temperature	3000 K / 4000 K	3000 K / 4000 K
Color Rendering Index	90	90
Lamp Efficacy	up to 90lm/W	up to 90lm/W
Lumen Maintenance Factor	70 %	70 %
Beam Angle	15D / 30D	15D / 30D
Equivalent to Metal Halide Lamp	35W PAR30 Metal Halide	50W PAR30 Metal Halide
Color Consistency	3-SDCM	3-SDCM
Remark	Not for enclosed fixture	Not for enclosed fixture

# PREMIUM PAR30 Pro - 20W

Dimmable



Website



Intelligent Driver

RA90

LM80

CE



Article Code	TPAR30PRO-20W-XD
Lamp Description	PREMIUM PAR30 20W - DIM
<b>GENERAL CHARACTERISTICS</b>	
Shape	PAR30
Cap - Base	E27
Rated Wattage	20 W
Input Voltage	220-240 Vac
Operating Frequency	50/60Hz
Luminous Flux	2000 lm
Lifetime (hours)	25,000 hrs
Switching Cycles	50,000
Start Time from 0% to 100%	< 0.5 s
Power Factor	0.9
Working Temperature	-20°C ~ 35°C
Guarantee	3 years
Dimension	W:95mm x H:125mm
<b>LIGHT CHARACTERISTICS</b>	
Color	Warm White / Neutral White
Color Temperature	3000 K / 4000 K
Color Rendering Index	90
Lamp Efficacy	up to 90lm/W
Lumen Maintenance Factor	70 %
Beam Angle	15D / 30D
Equivalent to Metal Halide Lamp	35W PAR30 Metal Halide
Color Consistency	3-SDCM
Remark	Not for enclosed fixture